

SOURCE: (C) WPI / DERWENT

AN : 1997-368365 [34] -

MC : A03-A01A A09-A08 A12-D00D A12-V03A D09-C02 D09-C03 D09-C04 D09-C04B
D09-C06 F03-C05 F04-C01 F04-D F04-E04

PN : JP9156012 A 19970617 DW199734 B32B5/26 027pp
- TW354251 A 19990311 DW199934 A61F13/15 000pp

PR : JP19950319396 19951207;JP19940328802 19941228;JP19940328854 19941228;
JP19950319397 19951207;JP19950319398 19951207

PA : (KAOS) KAO CORP

DC : A96 D22 F07 P32 P73


IC : A61F13/15 ;A61F13/46 ;B01J20/26 ;B32B5/26 ;D04H1/54 ;D04H13/00

TI : Absorbing sheet for sanitary napkin, medical pad, nappy etc. -
comprises highly absorbing polymer, bulky cellulosic fibre and
hydrophilic fine fibres.

AB : JP09156012 An absorbing sheet comprises at least a highly absorbing
polymer, bulky cellulosic fibre and hydrophilic fine fibres and is
composed of fibre aggregate and fibre web integrated with each other,
where the fibre aggregate has an absorbing surface and does not contain
the highly absorbing polymer on the side of the absorbing surface and
comprises mainly bulky cellulosic fibre having a fibre roughness of at
least 0.3 mg/m. The fibre web comprises a permeable layer comprising
mainly bulky cellulosic fibre of a fibre roughness of at least 0.3
mg/m. and a diffusion layer adjacent to the permeable layer comprising
bulky cellulosic fibre of fibre roughness of at least 0.3 mg/m. and
hydrophilic fine fibres and is adjacent to the fibre aggregate on the
side of the permeable layer. The highly absorbing polymer is contained
inside the absorbing sheet and is adhered to the fibres constituting
the absorbing sheet.

- USE - Used for a sanitary napkin, disposable nappy, medical pad, drip
sheet, absorbing sheet in kitchen, cleaning sheet, under sheet for bed,
etc..
- ADVANTAGE - The highly absorbing polymer is securely fixed inside of
the sheet, the highly absorbing polymer is slightly dropped out and the
highly absorbing polymer less generates gel blocking. The sheet has
three functions of permeation, diffusion and retention of liquid in one
absorbing sheet.
- (Dwg.1/17)

Best Available Copy



Best Available Copy

Patent Abstracts of Japan

PUBLICATION NUMBER : JP9156012
 PUBLICATION DATE : 17-06-1997
 APPLICATION NUMBER : JP19950319396
 APPLICATION DATE : 07-12-1995


VOL: 1997 NO: 10
 AB. DATE : 31-10-1997 PAT: A 9156012
 PATENTEE : KAO CORP
 PATENT DATE: 17-06-1997

INVENTOR : KUSAKAWA TETSUYA;
 KAWASAKI HIRONORI;
 HAMASHIMA YOSHIJI;
 NAKANISHI MINORU

INT.CL. : B32B5/26 ;
 A61F13/46 ;
 A61F13/15 ;
 B01J20/26 ;
 D04H1/54 ;
 D04H13/00

TITLE : ABSORPTIVE SHEET, ITS MANUFACTURE AND ABSORPTIVE ARTICLE

ABSTRACT : PROBLEM TO BE SOLVED: To fix a highly absorptive polymer and improve the absorption performance by embedding the highly absorptive polymer in spaces formed among fibers in the state of the fibers constituting an absorptive sheet being wet.
 SOLUTION: An absorptive sheet 100 is composed of fiber collective bodies 105 and fiber webs 108. The fiber collective bodies 105 are formed by bulky cellulose fibers 12 of fiber roughness of 0.3mg/m or more as a main component. On the other hand, fiber webs 108 are composed of heat permeable layers 107 composed of bulky cellulose fibers 12 of fiber roughness of 0.3mg/m or more as a main component and diffusion layers 109 adjoining the heat permeable layers 107 and containing the bulky cellulose fibers 12 of fiber roughness of 0.3mg/m or more and hydrophilic fine fibers 14. The fiber collective bodies 105 are integrated with the fiber webs 108. Also a highly absorptive polymer 106 is contained in an absorptive sheet 100 and bonded with the fibers constituting the absorptive sheet 100.



Best Available Copy

THIS PAGE BLANK (USPTO)

Best Available Copy